

US009636464B1

(12) United States Patent Binier

(10) Patent No.: US 9,636,464 B1 (45) Date of Patent: May 2, 2017

(54) DRUG DELIVERY DEVICE AND A DRUG INFORMATION DETECTION DEVICE

(71) Applicant: INNOVATIVE PRECISION INSTRUMENTS LIMITED, Hong

Kong (HK)

(72) Inventor: Richard Jean Marie Binier, Hong

Kong (HK)

(73) Assignee: Innovative Precision Instruments

Limited, Hong Kong (CN)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

0.3.C. 134(0) by 0 da

(21) Appl. No.: 15/225,259

(22) Filed: Aug. 1, 2016

(51) Int. Cl.

A61M 5/315 (2006.01)

A61M 5/24 (2006.01)

G06F 19/00 (2011.01)

A61M 5/20 (2006.01)

(52) U.S. Cl.

(58) Field of Classification Search

CPC A61M 5/31551; A61M 5/31573; A61M 5/31568; A61M 5/3157

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

5,739,775 A	* 4/1998	Brandestini G01D 5/2492			
		341/10			
6,277,099 B1	* 8/2001	Strowe A61M 5/31553 604/186			
7.008.399 B2	* 3/2006	Larsen A61M 5/142			
, ,		604/65			
(Continued)					

FOREIGN PATENT DOCUMENTS

CN	101862489 A	10/2010
CN	102413856 A	4/2012
	(Cont	inued)

Primary Examiner - Andrew Gilbert

(74) Attorney, Agent, or Firm — Kramer Amado, P.C.

(57) ABSTRACT

A drug delivery device which includes a first housing part, a second housing part, a button, a drug expelling mechanism, a graduated plate, a circuit board and a pressing rod. The button is connected to the first housing part. The drug expelling mechanism is disposed inside the second housing part, and includes a dose setting member which is rotatable and configured to set a drug dose to be expelled. The graduated plate is disposed inside the first housing part and connected to the button, and includes a first conductive element and a plurality of second conductive element disposed on a surface thereof. The plurality of second conductive elements are arranged in interval and the first conductive element is electrically connected to the plurality of second conductive elements. The circuit board is disposed inside the first housing part and connected to the dose setting member. The pressing rod is inserted through the graduated plate, and includes an end connected to the button and the other end movable on an axial direction to trigger the actuating switch.

21 Claims, 5 Drawing Sheets

